







Fidelis Network – Appliance Quick Specs (Rev J)

	CommandPost	10G	5G	1G	Collector SA2 Sandbox	Collector Controller 2	Collector XA2	Collector Controller 10G	Collector XA4	
										
Form Factor	1U HPE ProLiant DL360 Gen10 Chassis	2U HPE ProLiant DL560 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	2U HPE ProLiant DL380 Gen10 Chassis	
CPU	Dual Gold 6234 8/16-core 3.3Ghz	Quad Gold 6248 20/80-core 2.5Ghz	Dual Gold 6248 20/40-core 2.5Ghz	Dual Silver 4214 12/24-core 2.2Ghz	Dual Gold 6246 12/24-core 3.3Ghz	Dual Silver 4214 12/24-core 2.2Ghz	Dual Gold 6234 8/16-core 3.3Ghz	Dual Gold 6248 20/40-core 2.5Ghz	Dual Gold 6246 12/24-core 3.3Ghz	
TPM	No	No	No	No	No	No	No	No	No	
Memory	128GB ECC DDR4 2933Mhz	384GB ECC DDR4 2933Mhz	128GB ECC DDR4 2933Mhz	64GB ECC DDR4 2933Mhz	192GB ECC DDR4 2933Mhz	64GB ECC DDR4 2933Mhz	128 GB ECC DDR4 2933Mhz	128 GB ECC DDR4 2933Mhz	192 GB ECC DDR4 2933Mhz	
Storage Capacity & Configuration	600 GB (3 TB Effective) 6x HDD, RAID-5	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1 ----- 1.2 TB (3.6 TB Effective) 6x HDD, RAID-10	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1 ----- 1.2 TB (3.6 TB Effective) 6x HDD, RAID-10	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1 ----- 1.2 TB (13.2 TB Effective) 22x HDD, RAID-10	
Network Adapters	4x 1GbE	4x 1GbE 4x 10GbE optical (inline capable)	4x 1GbE 4x 10GbE optical (inline capable)	4x 1GbE 4x 1GbE (inline capable)	4x 1GbE	4x 1GbE	4x 1GbE	2x 10GbE Fiber 4x 1GbE	2x 10GbE Fiber 4x 1GbE	
Out of Band Management	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	
Dimensions	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 8.75 cm (3.44 in) W: 44.54 cm (17.54 in) D: 75.47 cm (29.71 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 8.73 cm (3.44 in) W: 44.54 cm (17.54 in) D: 67.94 cm (26.75 in)
Weight (appx.)	16.27 kg (35.86 lb)	34.12 kg (75.23 lb)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	24.5 kg (54 lb)	
Power Supply	Dual hot-swap 500W High Efficiency AC power supplies	Four hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	
Operating Temperature	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level
AC Input Requirements	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC
BTU Rating (max)	1902 BTU/hr (100 VAC) 1840 BTU/hr (200 VAC) 1832 BTU/hr (240 VAC)	3207 BTU/hr (100 VAC) 3071 BTU/hr (200 VAC) 3112 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)

Fidelis Deception - Appliance Quick Specs (Rev J)

Fidelis Decryption - Appliance Quick Specs (Rev J)

	FDH-3000	FDH-1000		TLS-5G	TLS-25G
					
Form Factor	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis	Form Factor	1U HPE ProLiant DL360 Gen10 Chassis	1U HPE ProLiant DL360 Gen10 Chassis
CPU	Dual Gold 6234 8/16 -core 3.3Ghz	Dual Silver 4214 12/24-core 2.2Ghz	CPU	Dual Silver 4214 12/24-core 2.2Ghz	Dual Gold 6248 20/40-core 2.5Ghz
TPM	No	No	TPM	TPM 2.0	TPM 2.0
Memory	128GB ECC DDR4 2933Mhz	64GB ECC DDR4 2933Mhz	Memory	64GB ECC DDR4 2933Mhz	128GB ECC DDR4 2933Mhz
Storage Capacity & Configuration	600 GB (3 TB Effective) 6x HDD, RAID-5	300 GB 2x HDD RAID-1	Storage Capacity & Configuration	300 GB 2x HDD RAID-1	300 GB 2x HDD RAID-1
Network Adapters	4x 1GbE 2x 10GbE optical	4x 1GbE 2x 10GbE Optical	Network Adapters	4x 1GbE 4x 1/10GbE 2x 10GbE 6x 1G/10G Optical SFP+	4x 1GbE 4x 1/10/25GbE 2x 10GbE 6x 25G/10G Optical SFP+
Out of Band Management	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	Out of Band Management	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates	3 Year ILO- HPE Advanced 24x7 Tech Support and Updates
Dimensions	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	Dimensions	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)	H: 4.29 cm (1.69 in) W: 43.46 cm (17.11 in) D: 70.7 cm (27.83 in)
Weight (appx.)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)	Weight (appx.)	16.27 kg (35.86 lb)	16.27 kg (35.86 lb)
Power Supply	Dual hot-swap 500W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies	Power Supply	Dual hot-swap 800W High Efficiency AC power supplies	Dual hot-swap 800W High Efficiency AC power supplies
Operating Temperature	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level	Operating Temperature	10° to 35°C (50° to 95°F) at sea level	10° to 35°C (50° to 95°F) at sea level
AC Input Requirements	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC	AC Input Requirements	100 - 120 VAC 200 - 240 VAC	100 - 120 VAC 200 - 240 VAC
BTU Rating (max)	1902 BTU/hr (100 VAC) 1840 BTU/hr (200 VAC) 1832 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	BTU Rating (max)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)	3067 BTU/hr (100 VAC) 2958 BTU/hr (200 VAC) 2949 BTU/hr (240 VAC)